



CONVERTOR

FLANGE	JIS5K 65A
MATERIAL	ALUMINUM CASTING
OUTSIDE DIAMETER	φ 155
DIAMETER OF BOLT CIRCLE	φ 130
DIAMETER OF BOLT HOLES	φ 15
NUMBER OF BOLT HOLES	4
THICKNESS	12

型式	ℓ	ℓ ₁	ℓ ₂	ℓ ₃	NOTE	Q'ty	MODEL	ℓ	ℓ ₁	ℓ ₂	ℓ ₃	NOTE	Q'ty
TSE-A4SA-025	250	100	50	100			TSE-A4SA-065	650	150	50	450		
TSE-A4SA-030	300	100	50	150			TSE-A4SA-070	700	150	50	500		
TSE-A4SA-035	350	100	50	200			TSE-A4SA-075	750	150	50	550		
TSE-A4SA-040	400	100	50	250			TSE-A4SA-080	800	150	50	600		
TSE-A4SA-045	450	100	50	300			TSE-A4SA-085	850	150	50	650		
TSE-A4SA-050	500	100	50	350			TSE-A4SA-090	900	150	50	700		
TSE-A4SA-055	550	150	50	350			TSE-A4SA-095	950	150	50	750		
TSE-A4SA-060	600	150	50	400			TSE-A4SA-100	1000	150	50	800		

○ (Required length)

○ (Required length)

INTRINSIC SAFETY TYPE OF EXPLOSION-PROTECTION
Explosion class and Ignition of explosive gases:ia3nG5

a reduced drawing (A3size~)

Q'ty:

図章 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN	名称 TITLE
			takahashi	TSE-A4SA-□ CAPACITANCE TYPE LEVEL SENSOR
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Sep,26,2016	図面番号 DRG. No. HE-14018
			東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.	