



\*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○ (Required power supply)

MICRO SWITCH  
250V AC 5A RESISTIVE LOAD  
COLOR: 10YR7.5/14  
DETECTION TORQUE: About 10.0N·cm  
REVOLUTION: 1RPM  
AMBIENT TEMPERATURE: -10~+40°C

\*Please specify the length.

Q	NOTE	Q'ty
200		
250		
300		
350		
400		
450		
500		
550		
600		

Q	NOTE	Q'ty
650		
700		
750		
800		
850		
900		
950		
1000		
2000		
3000		

○ (Required length)

\*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	$\phi 11 \sim \phi 12$
GEUL10-G P2	$\phi 10 \sim \phi 11$
GEUL10-G P3	$\phi 9 \sim \phi 10$
GEUL10-G P4	$\phi 8 \sim \phi 9$

○ (Required cable gland)

APPRICATION RANGE: Ex d IIB T4 Gb  
APPROVAL No.: TC22542X  
EXPLOSION-PROTECTED CONSTRUCTION: d  
EXPLOSION CLASS: IIB  
Temperature class: T4

Q'ty:

図番 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN	名称 TITLE
			takahashi	PADDLE TYPE TPE-101F LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Jan,21,2020	図面番号 DRG. No. HR-95016
東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.				