



\*Please specify the power supply type.

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-6-WP
AC200V	PRL-6-VP

○ (Required power supply)

MICRO SWITCH  
250V AC 5A RESISTIVE LOAD

COLOR : 10YR7.5/14  
DETECTION TORQUE : About 10.0N · cm  
REVOLUTION : 1RPM  
AMBIENT TEMPERATURE : -10 ~ +40°C

\*Please specify the length.

∅	NOTE	Q'ty
200		
250		
300		
350		
400		
450		
500		
550		
600		

  

∅	NOTE	Q'ty
650		
700		
750		
800		
850		
900		
950		
1000		
2000		
3000		

○ (Required length)

\*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
GEUL10-G P1	φ 11 ~ φ 12
GEUL10-G P2	φ 10 ~ φ 11
GEUL10-G P3	φ 9 ~ φ 10
GEUL10-G P4	φ 8 ~ φ 9

○ (Required cable gland)

APPRICATION RANGE : Ex d IIB T4 Gb  
APPROVAL No. : TC22542X  
EXPLOSION-PROTECTED CONSTRUCTION: d  
EXPLOSION CLASS: IIB  
Temperature class: T4

Q'ty :

図番 CHANGE NOTICE 承認 APPROVED 検図 CHECKED 製図 DRAWN takahashi	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Jan,21,2020	Temperature in the tank : Max.200°C	名称 TITLE PADDLE TYPE TPE-201F LEVEL SWITCH
				東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.	図面番号 DRG. No. HR-95020